

10 8 FEB 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)


PCT

(10) International Publication Number
WO 2004/014619 A1

- (51) International Patent Classification⁷: **B26D 7/00**
- (21) International Application Number: **PCT/FI2003/000594**
- (22) International Filing Date: **7 August 2003 (07.08.2003)**
- (25) Filing Language: **Finnish**
- (26) Publication Language: **English**
- (30) Priority Data:
20021454 **8 August 2002 (08.08.2002)** **FI**
- (71) Applicant (for all designated States except US): **METSO PAPER, INC. [FI/FI]; Fabianinkatu 9 A, FIN-00130 HELSINKI (FI).**
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **ALATALO, Jukka [FI/FI]; Satukalliontie 20, FIN-04430 JÄRVENPÄÄ (FI). HEIKOLA, Asko [FI/FI]; Ilveksentie 4, FIN-05400 JOKELA (FI).**
- (74) Agent: **FORSSÉN & SALOMAA OY; Eerikinkatu 2, FIN-00100 HELSINKI (FI).**
- (81) Designated States (national): **AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**

[Continued on next page]

(54) Title: **METHOD AND DEVICE FOR CALIBRATING THE POSITION OF BLADES OF A SLITTER-WINDER OF A PAPER OR BOARD MACHINE**



(57) Abstract: The invention relates to a method for calibrating the position of blades of a slitter-winder of a paper or board machine, which blades (11,12) are attached to blade carriages (11A,12A) or the like disposed on guides (14,13) or the like, in which method the position of the blades (11,12) of the slitter-winder is measured by means of a multipoint measurement method, whereby the position of the blade carriage (11A,12A) of the respective blade (11,12) is measured. In the method the position of the blades (11,12) is calibrated with a calibration tool (20). A positioning member (21) of the calibration tool (20) is arranged to touch a slitting edge (17) of the blade (11) to be calibrated. The position of the calibration tool (20) is measured by means of the multipoint

measurement method and the position of the slitting edge (17) of the blade (11) is determined based on the measurement result of the position of the calibration tool (20). The invention also relates to a device for calibrating the position of blades of a slitter-winder of a paper or board machine, which device is disposed in connection with the slitter-winder of the paper or board machine, which slitter-winder comprises pairs of blades comprising a top blade (12) and a bottom blade (11), attached to their respective blade carriages (11A,12A) arranged to be movable along a guide (14,13) or the like, in connection of which slitter-winder means (15,16,18,19) are arranged for measuring the position of the blades (11, 12). In the method the device used for calibrating the position of the blades (11,12) is a calibration tool (20) which is arranged to be attached to the same guide (14) with the blade (11) to be calibrated. The calibration tool (20) comprises a means (21) for indicating the slitting edge (17) of the blade (11) and means (23,16) for measuring the position of the calibration tool (20).

WO 2004/014619 A1